



Large superconducting wind turbine generators: Driving the cost down?

Abrahamsen, Asger Bech; Magnusson, N.; Jensen, Bogi Bech; Runde, M.

Publication date:
2012

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Abrahamsen, A. B., Magnusson, N., Jensen, B. B., & Runde, M. (2012). *Large superconducting wind turbine generators: Driving the cost down?*. Abstract from 9th Deep Sea Offshore Wind R&D Seminar, Trondheim, Norway.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Large superconducting wind turbine generators

A.B. Abrahamsen¹, N. Magnusson², B.B. Jensen³ and M. Runde^{2,4}

**¹Materials research Division, Risø DTU, Technical University of Denmark, Roskilde,
Denmark (asab@risoe.dtu.dk)**

²SINTEF Energy Research, Trondheim, Norway

**³Department of Electrical Engineering, Technical University of Denmark, Lyngby,
Denmark**

**⁴Department of Electric Power Engineering, Norwegian University of Science and
Technology, Trondheim, Norway**

Topic: New turbine and generator technology

To realize large (>10 MW) direct-driven offshore wind turbines, a number of steps are needed to reduce weight, volume and cost compared to standard technologies. One of these steps can be to introduce superconductor materials, carrying high current densities, in the generator to achieve a compact and light-weighted construction. In this paper we discuss the basics for superconductor generator technology and state-of-the-art of superconductor wire material options, as well as some challenges for the superconductor industry to overcome. Only the rotor carrying a DC current is replaced with superconductor materials. Analytical calculations and FEM-based simulations are used to set the governing superconductor generator conditions. A 5 MW superconducting wind turbine generator forms the basics for the feasibility considerations, defining requirements on performance and costs of superconducting wires, particularly for the YBCO and MgB₂ superconductors currently entering the commercial market. Initial results indicate that a 5 MW generator with an active weight of 34 tons, diameter of 4.2 m and length of 1.5 m can be realized using superconductors carrying 300 A/mm² in a magnetic field of 4 T. This is a significant weight reduction compared to conventional drive train solutions. The results are compared to the performance of available superconductors, as well as the near future forecasted performance.

Filename: large superconducting wind turbine generators_abstract.doc
Directory: C:\Documents and Settings\asab\Local Settings\Temporary Internet Files
Template: C:\Documents and Settings\asab\Application
Data\Microsoft\Templates\Normal.dotm
Title:
Subject:
Author: Ole Gunnar Dahlhaug
Keywords:
Comments:
Creation Date: 9/12/2011 12:32:00 PM
Change Number: 5
Last Saved On: 9/12/2011 1:05:00 PM
Last Saved By: Niklas Magnusson
Total Editing Time: 4 Minutes
Last Printed On: 2/7/2012 2:55:00 PM
As of Last Complete Printing
Number of Pages: 1
Number of Words: 287 (approx.)
Number of Characters: 1,641 (approx.)